

Overview


ADS-31 PIEZOELECTRIC STRAIN SENSOR



- Suitable for all ARTIS monitoring systems
- Integrated piezo load amplifier
- High sensitivity
- One-dimensional measuring direction
- Easy mounting
- Sensor cable can be laid easily in the machine
- Resistant PUR-sheet








Application example:


ADS-31 and CFM-4 measuring transducer with the CTM Tool and Process Monitoring System.



Application example:

ADS-31 and GEM**FM**01 force measuring transducer with the GENIOR MODULAR Tool and Process Monitoring System.





ARTICLE NUMBER		
CODE	03PZ021100x	(x = see variants)
VARIANTS		
ADS-31, 5 M CABLE	03PZ0211007	
ADS-31, 15 M CABLE	03PZ0211008	
ADS-31, 25 M CABLE	03PZ0211009	

DIMENSIONS	see drawing
WEIGHT	
ADS-31, 5 M CABLE	0.432 kg
ADS-31, 15 M CABLE	0.868 kg
ADS-31, 25 M CABLE	1.261 kg
MATERIAL	
INNER PART	Chromium nickel steel
SHEAT	PUR-sheat, resistant to cooling lubricants
DEGREE OF PROTECTION	IP66/IPx7 resistant to cooling lubricants
OPERATING TEMPERATURE	10 °C +50 °C

CABLE LENGTHS	see variant
WIRE BREAK DETECTION	in the dedicated measuring transducer
MEASURING SECTION	55 mm
VOLTAGE SUPPLY	-15 V DC / 0 V / +15 V DC
OUTPUT SIGNAL	± 10 V
ACTIVATION	+5 V DC
CONFORMITY	CE, UKCA

PU CABLE		
CABLE TYPE	PU cable, suitable for drag chains	
DIAMETER	6 mm	
CONDUCTOR SIZE	(AWG 26)	
BENDING RADIUS	7.5 x cable diameter	
WIRE CONFIGURATION	Conductor, fine wired acc. to VDE 0295	



For a full list of address locations, please consult the Marposs official website

ODN6403EN01 – Edition 04/2022 – Specifications are subject to modifications © Copyright 2010-2022MARPOSS S.p.A. (Italy) – All rights reserved.

Marposs has an integrated system for Company quality, environmental and safety management, with ISO 9001, ISO 14001 and OHSAS 18001 certification.





Download the latest version of this document