




IRIX

CPS1

CHROMATIC CONFOCAL SOLUTION



MARPOSS

Controllers	Spec.
Measuring frequency	up to 2.000 Hz
Light source	LED
Wavelength range	[450 ÷ 700] nm
Measuring modes	Distance Thickness
Calibration tables (max)	32
Encoders input	3 digital (TTL/HTL Differential/Single Ended)
Digital ports	USB / ETH / RS422
Analog outputs	2 (0-10Vdc)
Synchronization I/O	1 Synchro input (TTL) / 1 Synchro output (TTL)
Optical fiber connector	FC/APC
Compatible Optical pens	all the ones will be required (for application dedicated solution)
Power supply / consumption	24 V DC / 20 W
Protection type	IP40
Dimensions (w x h x d)	235 x 142,5 x 130 mm
Mechanical interface	with support feet

Optical pen	Meas.unit	Spec.
Measuring range	[μ m]	4.000
Working distance	[mm]	16,5
Max. object slope (1)	[deg]	+/- 21°
Axial model	-	Standard
Radial model	-	Optional
LATERAL (XY) PROPERTIES		
Spot size (diameter) (3)	[μ m]	8
Lateral resolution	[μ m]	4
MECHANICAL INTERFACE		
Length	[mm]	128
Diameter	[mm]	27
Weight	[g]	153
RESOLUTION (1)		
[no average]	[nm]	110
[with average 10]	[nm]	37
Accuracy	[nm]	300
THICKNESS MEASUREMENT (2)		
Min. measurable thickness	[μ m]	110
Max measurable thickness	[μ m]	5700

Note:

(1) all value are referred to GOLD MIRROR target

(2) the values are referred to refractive index 1,5 in the following conditions:
optimal rate, no averaging, middle of the measuring range

(3) indicative value by design

For a full list of address locations, please consult the Marposs official website

Edition 04/2021 - Specifications are subject to modifications. © Copyright 2017-2021 MARPOSS S.p.A. (Italy) - All rights reserved.

MARPOSS, Logo and Marposs product names/signs mentioned or shown herein are registered trademarks or trademarks of Marposs in the United States and other countries. The rights, if any, of third parties on trademarks or registered trademarks mentioned in the present publication are acknowledged to the respective owners.

Marposs has an integrated system to manage the Company quality, the environment and safety, attested by ISO 9001, ISO 14001 and OHSAS 18001 certifications.

Some of the items supplied by Marposs S.p.A., or parts of them, may be subject to export control if exported outside the European Union, or may be subject to restrictive measures adopted by the competent national, supranational or international authorities. Buyer of the items delivered by Marposs S.p.A. shall comply with all applicable export control and sanctions laws and regulations.