

For a full list of address locations, please consult [www.marpoSS.com](http://www.marpoSS.com).  
MARPOSS and MarpoSS are either registered trademarks or trademarks of MarpoSS in the United States and other countries. The rights, if any, of third parties on trademarks or registered trademarks mentioned in the present publication are acknowledged to the respective owners.  
MARPOSS and MarpoSS product marks/signs mentioned or shown herein are registered trademarks or trademarks of MarpoSS S.p.A. (Italy) - All rights reserved.  
Specifications are subject to modifications - © Copyright 2014 MarpoSS S.p.A.



USB DEVICE

RS232 SERIAL PORT

ETHERNET 10/100

24 VDC

4xUSB HOST CONNECTORS

- ★ SIZE: 230x180x45 mm (9"x7"x1.8") LxHxD
- ★ 8.4" COLOR TFT LCD DISPLAY
- ★ SPECIFICALLY DESIGNED FOR THE SHOP FLOOR ENVIRONMENT
- ★ IP65 FRONT PANEL
- ★ TOUCH SCREEN

**ACTUAL SIZE**



**Merlin**

**MARPOSS**



Merlin

MARPOSS

## Main software characteristics:

- \* Remote data storage through Ethernet LAN or through a removable USB memory device or local data storage on internal memory
- \* Data storage format: .DFQ (Q-DAS® qs-STAT®), .CSV (Microsoft® Excel Comma Separated Values) and Sesame
- \* Sensors connectable via USB, RS232 or Bluetooth® wireless technology
- \* Data collection from Marposs® data acquisition devices and third party devices
- \* Multiple measurement capability with numeric and graphical displays
- \* Statistical analysis with graphical display (Histogram, Control Charts, Value Chart) and numeric summary (Cp, Cpk, Spread, Average)
- \* Printing capabilities through standard printers available on the market
- \* Part Counters
- \* Batch data management

