



ETHERNET SWITCH 005

Special Features

- Unmanaged Ethernet switch for bus- and star topologies
- Five RJ45-jacks
- Plug & play device
- Autonegotiation
- MDI/MDIX autocrossover function
- Insulation between TP ports

Ethernet Switch 005 O4701700501	
Dimensions (H x W x D)	100 mm x 45 mm x 87 mm
Weight	0.175 kg
Connection via twisted pair	5 x RJ45-jack with MDI-X-assignment 10/100 MBit/s (half-/ full duplex)
Connection for power supply	1 x 3-pin plug-in terminal block
Mounting	on standard mounting rail acc. to DIN EN 60715
Power supply	24 V DC (19.2 – 28.8 V DC)
Max. power loss 24 V DC	2.4 W

Max. current consumption	100 mA
Overcurrent protection at input PTC resettable fuse	0.6 A / 60 V
Permitted cable length	max. 100 m
Operating temperature	-10 ... +60 °C (rel. humidity in operation < 95%, no condensation)
Storage/transport temperature	-40 ... +80 °C
Degree of protection	IP20
Conformity	CE



www.marposs.com

For a full list of address locations, please consult the Marposs official website

ODN6AE0EN12 – Edition 11/2016 – Specifications are subject to modifications
© Copyright 2016 ARTIS GmbH (Germany) – All rights reserved.

ARTIS and ARTIS product names/signs mentioned or shown herein are registered trademarks or trademarks of ARTIS in the United States and other countries. The rights, if any, of third parties on trademarks or registered trademarks mentioned in the present publication are acknowledged to the respective owners.

ARTIS has a quality management system, attested by ISO 9001:2008 certification.



Download latest version of this document