

M62Flex

ENGAGE WITH
FLEXIBILITY



MARPOSS

Manual use bench gauge with multiple contact turrets suitable for the inspection of **DOB (Mdk)**, **Major Diameter** and **Minor Diameter** on External Gears with flexibility to measure parts with external diameter up to 180 mm.

TECHNICAL FEATURES


Gear External Diameter (De)	30 ÷ 180 mm
Gear Height (H)	15 ÷ 40 mm
Gear Module (m)	1 ÷ 4
Number of Contacts per Turret	Up to 6

FLEXIBILITY

The use of SMAC-MCA moving coil actuators gives the possibility to measure, in one gauge, gears with different diameters without any mechanical retooling.

SOFT-LAND™ TECHNOLOGY

The use of an appropriate software allows the measuring groups to approach the surface of the teeth with a controlled low force while monitoring their position error. This is identified as the proper solution to avoid damages and marks on parts.




Ease of use and retool

DATA

The system has the ability to log and verify data as the process is been carried out.

SAFE AND ENERGY EFFICIENT

The gauge operates at low current, typical at less than 2A.



For a full list of address locations, please consult the Marposs official website

Edition 04/2019 - Specifications are subject to modifications © Copyright 2018 - 2019 MARPOSS S.p.A. (Italy) - All rights reserved.

MARPOSS, logo and Marposs product names/signs mentioned or shown herein are registered trademarks or trademarks of Marposs in the United States and other countries. The rights, if any, of third parties on trademarks or registered trademarks mentioned in the present publication are acknowledged to the respective owners.

Marposs has an integrated system to manage the Company quality, the environment and safety, attested by ISO 9001, ISO 14001 and OHSAS 18001 certifications.